

Program for IIB Derivative Corrections

Gordon Chalmers

e-mail: gordon@quartz.shango.com

Abstract

A Matlab program is presented that computes derivative corrections in the S-dual invariant formulation for IIB graviton scattering to any order in perturbation theory. The coefficients of the four-point function are produced, pertaining to the non-logarithmic terms. The program can be modified to find coefficients of the higher-point functions. Instantons have not explicitly been included.

The graviton scattering amplitude in IIB superstring theory has been investigated recently in the context of manifesting S-duality. This manifestly S-dual graviton scattering has been analyzed systematically in [1], and references therein.

This text contains a computing program that automates the perturbative calculations. To any order in derivatives this program computes the analytic portion of the graviton scattering, in the flat ten-dimensional superstring theory. The D-instantons are allowed to be included, but their form is not placed in the program.

The program is written in Matlab, and follows the procedure in [1] by partitioning numbers and attaching weighted trees to these numbers.

Given the large number of papers on the topic, the author decided to place it on the archive. The Matlab program may be found by downloading the TeX source.

The quantum gravitational action may be numerically studied with this program, at the $\Box^k R^4$ level, with any set of integers k .

References

- [1] Gordon Chalmers, *Symmetry Algebra of IIB Superstring Scattering*, physics/0510233.

Matlab Program

```
clear all

Nmin=1; Nmax=10;

trialnumber=200;

yp=0; flagno=1;

nullcase=0;

trialnumber=200

for i=Nmin:Nmax
for j=1:round(Nmax/3)
Oone(i)=0; Partitiontype(i,j)=0;
end
end

for N=1:Nmax
for Np=1:round(Nmax/3);
x(1,1)=0; p(1,1)=0; rp(1,1)=0; flagnumber(1)=0;
nullcase=0; a=0; dimp=0; flagno=0; timem=0;
totalflagno=0; v(1)=0; yp=0;
clear x,p,rp,flagnumber,nullcase;
clear a,dimp,flagno;
clear timem,totalflagno,v,yp;
clear i
if Np=N
x(1,1)=0; clear x p(1,1)=0; clear p
for j=1:trialnumber
for i=1:Np
x(i,j)=0; p(i,j)=0;
end
end
end
```

```

for j=1:trialnumber
    flagno=1; timem=0; nullcase=0;
    while flagno==1
        yp=0;
        for i=1:Np
            x(i,j)=2*round(((N-1)/2-1)*rand)+3;
            yp=yp+x(i,j);
        end
        flagno=1;
        if yp==N
            p(:,j)=x(:,j);
            flagno=0;
        end
        timem=timem+1;
        if timem>trialnumber
            flagno=0;
            nullcase=1;
        end
        if nullcase==1
            sp=0;
            j=101;
        end
    end
    if nullcase ==1
        for j=1:trialnumber
            for m=1:trialnumber
                for a=1:Np

```

```

for b=1:Np
    if a\|b
        if p(a,j)\|p(b,j)
            test1=p(a,j); test2=p(b,j);
            p(b,j)=test1; p(a,j)=test2;
        end
    end
end
end
end
end
end
v=size(p); dimp=v(2);
for i=1:dimp
    flagnumber(i)=0;
end
for i=1:dimp
    for m=1:dimp
        if m==i
            flagnumber(m)=1;
        end
        if m ==i
            if p(:,m)==p(:,i)
                if i\|m
                    flagnumber(m)=0;
                else flagnumber(m)=1;
            end
        end
    end
end
end

```

```

end
end
totalflagno=0;
for i=1:dimp
totalflagno=totalflagno+flagnumber(i);
end
rp(1,1)=0; clear rp
for i=1:totalflagno
for j=1:Np
rp(j,i)=0;
end
end
sp=0; k=0;
for i=1:dimp
if flagnumber(i)==1
k=k+1;
rp(:,k)=p(:,i);
sp=sp+1;
end
end
sp2=sp; test=0;
for k=1:sp2
for l=1:Np
test=test+rp(l,k);
end
end
sp=test/N
end

```

```

end
for i=1:Np
Partitiontype(1,i)=0; Partitiontype(2,i)=0;
end
Partitiontype(N,Np)=sp;
end
for j=1:Np
Oone(N)=Oone(N)+Partitiontype(N,j);
end
clear sp;
end
Nmin=1; Nmax=10;
clear i
tau=i*1;
tau1=real(tau); tau2=imag(tau);
trialnumber=200;
A1=1;A2=1;
for i=1:Nmax
tensorc(i)=1;
end
for i=1:Nmax
for j=1:round(Nmax/3)
Amp(i,j)=0;
end
end
for N=1:Nmax
for Np=1:round(Nmax/3);
if Partitiontype(N,Np) =0

```

```

yp=0; flagno=1;
nullcase=0;
x(1,1)=0; p(1,1)=0; rp(1,1)=0; flagnumber(1)=0;
nullcase=0; a=0; dimp=0; flagno=0; timem=0;
totalflagno=0; v(1)=0; yp=0;
clear x,p,rp,flagnumber,nullcase;
clear a,dimp,flagno;
clear timem,totalflagno,v,yp;
if Np_i=N
x(1,1)=0; clear x p(1,1)=0; clear p
for j=1:trialnumber
for i=1:Np
x(i,j)=0; p(i,j)=0;
end
end
for j=1:trialnumber
flagno=1; timem=0; nullcase=0;
while flagno==1
yp=0;
for i=1:Np
x(i,j)=2*round(((N-1)/2-1)*rand)+3;
yp=yp+x(i,j);
end
flagno=1;
if yp==N
p(:,j)=x(:,j);
flagno=0;
end

```



```

timem=timem+1;
if timem<trialnumber
    flagno=0;
    nullcase=1;
end
if nullcase==1
    sp=0;
    j=101;
end
end
end
if nullcase =1
    for j=1:trialnumber
        for m=1:trialnumber
            for a=1:Np
                for b=1:Np
                    if a<b
                        if p(a,j)>p(b,j)
                            test1=p(a,j); test2=p(b,j);
                            p(b,j)=test1; p(a,j)=test2;
                        end
                    end
                end
            end
        end
    end
end
v=size(p); dimp=v(2);
for i=1:dimp

```

```

flagnumber(i)=0;
end
for i=1:dimp
for m=1:dimp
if m==i
flagnumber(m)=1;
end
if m =i
if p(:,m)==p(:,i)
if i<m
flagnumber(m)=0;
else flagnumber(m)=1;
end
end
end
end
end
totalflagno=0;
for i=1:dimp
totalflagno=totalflagno+flagnumber(i);
end
rp(1,1)=0; clear rp
for i=1:totalflagno
for j=1:Np
rp(j,i)=0;
end
end
sp=0; k=0;

```

```

for i=1:dimp
if flagnumber(i)==1
k=k+1;
rp(:,k)=p(:,i);
sp=sp+1;
end
end

instanton=0;
w=size(rp)
dimbase2N=w(1);
Q=0;
AmpNNp=0;
for m=1:w(2)
R(m)=0; T(m)=1;
end
for i=1:dimbase2N
S(i)=0; zs(i)=0;
end
for m=1:w(2)
if rp(:,m) ==0
for i=1:dimbase2N
zs(i)=rp(i,m);
end
for A=1:base2N
Q=A-1;
for l=1:dimbase2N
if l ==dimbase2N
Q=P;

```

```

end
if l==dimbase2N
if Q==1
a(1)=1;
end
if Q==0
a(1)=0;
end
end
end
k=N-3;
s=3/2+(N-3)/2;
if mod(k,2)==0
gmax=1/2*(k+2);
end
if mod(k,2)==1
gmax=1/2*(k+1);
end
for i=1:dimbase2N
if a(i)==0
if instanton==1
S(i)=0;
end
end
if a(i)==1
if instanton==1
S(i)=0;
end

```

```

end
T(m)=T(m)*S(i);
end
end
R(m)=R(m)+T(m);
end
end
end
end
for c=1:w(2)
Amp(N,Np)=Amp(N,Np)+R(c);
AmpNNp=AmpNNp+R(c);
end
end
end
end
for i=1:Nmax
Coeff(i)=0;
for j=1:round(Nmax/3)
Coeff(i)=Coeff(i)+tensorc(i)*Amp(i,j);
end
end
end

```